


The Cutter Soil Mixing developed by **TEC SYSTEM** is the unique and patented tool allowing multi-carrier installation. It is very versatile both in terms of the number of possible assemblies and its technical capabilities.






- Wet mixing only
 Based on Hydrofraise
 Technology
- Mixing energy concentrated on bottom part of tool
- High mixing quality
 Very low grout pressures
- No vibrations
 Verticality control in real time
- Incorporation of relatively low volumes : less waste

CSM CONSTRUCTION SEQUENCE

• Primary / Secondary sequence for walls





CUTTER SOIL MIXING

GUIDES SELECTION


Туре	CSM
Brand	TEC SYSTEM
Depth achieved (m)	Up to 35m

KELLY

The KELLY is composed by a base element combined with general extensions. The combination must comply with carried stroke.

Base KELLY (m)	11
KELLY extension (m)	3-4-5-6-7-8-8,5-9-10

Low Top	Simple Rot.	Standard	Regrip
Fixed	•	•	
Rotating			



EUNDEX

F3500

PERFORMANCES

CUTTER HEADS				
Types	HT5000	HT7500		
Length (mm)	2400/2800	2400/2800		
Width (mm)	450/800	500/1200		
Maximumpressure (bar)	320	320		
Torque (kNm)	50	75		
Displacement (I)	10	15		
Speed (rpm)	0 to 45*	0 to 30*		
Power (kW)	0 to 150*	0 to 170*		

^{*} Depending on carrier capabilities

CARRIERS

Λ II Λ		-11M	
			RIERS


Band	Rig	Engine power	Depht /regrip	Max Mix	Max Mix
	9	gs p ss.	236111/132116	speed HT5000	speed HT7500
	B200 XP-2	470 kW - 630 hp	19,2 m	31 rpm	21 rpm
	B250 XP-2	336 kW - 456 hp	22,1 m	31 rpm	21 rpm
casagrande	B300 XP-2	336 kW - 456 hp	22,8 m	31 rpm	21 rpm
	B360 XP-2	450 kW - 603 hp	23,3 m	40 rpm	27 rpm
	B470 XP-2	563 kW - 754 hp	30 m	40 rpm	27 rpm
	CV22-F	563 kW - 754 hp	21,8 m	40 rpm	27 rpm
ABI	TM22 on SR 35T	470 kW - 640 hp	21,5 m	40 rpm	27 rpm
	TM22 on SR 45T	563 kW - 754 hp	21,5 m	45 rpm	30 rpm
EQUIPMENT LTD	TM26 on SR 45T	563 kW - 754 hp	25,5 m	45 rpm	30 rpm
	SM 18/22 HD on SR 45T	563 kW - 754 hp	21,5 m / 30 m	45 rpm	30 rpm
	LRB 155	450 kW - 603 hp	21,0 m	35 rpm	23 rpm
LIEBHERR	LRB 255	670 kW - 911 hp	21,0 m	40 rpm	26 rpm
	LRB 355.1	600 kW - 816 hp	23 m / 35 m	43 rpm	28 rpm
	LRB 23	600 kW - 816 hp	21,6 m	32 (40) rpm	21(30) rpm

585 kW - 794 hp

35,0 m


40 rpm

27 rpm















CS/M Applications



Deep Soil Mixing



Ground consolidation



Waterproof barrier



CSM

BINDER PLANT



FEATURES

CSM BINDER PLANT			
Capacity	20 m3/h		
Mixer volume	1 200 l		
Agitator volume	3000 I		
Pump Capacity/ Maximum pressure	800 l/min @ 25 bar		





after-sales service

A responsive service directly on your construction sites

Our technicians support our clients from **commissioning to technical support** in case of any issue with our equipment.

Our teams are mobile and can bring their expertise (hydraulic, mechanical, electrical, electronic) directly to your construction sites to address project emergencies

Available and responsive, we meet your needs in a timely manner thanks to a dedicated team.





spare parts

To minimize the downtime of your machines, TEC System has a large stock of spare parts for its entire range of equipment.

Reliable and local suppliers

To offer our clients the best cost/availability balance for our spare parts.

Delivered the day after your order.

We ensure delivery in France the next day before 1:00 PM for all orders placed before 3:00 PM.

A high-performing purchasing service

our promise

Delivering high-performance machines that are robust, reliable, innovative, and versatile, enabling you to carry out your construction projects with complete peace of mind.



TEC SYSTEM

14 rue Émile Zola - 86530 NAINTRÉ
FRANCE

info@tecsystem.fr

+33 (0)5 49 93 76 00

www.tecsystem.fr Linkedin

